

Technical data

IDA-5 Infusion Device Analyzer

Fast. Accurate. Proven.

Ensure infusion pumps are tested accurately and quickly with the IDA-5 Infusion Device Analyzer. The IDA-5 is based on sophisticated measurement technology trusted by biomedical professionals around the world for over 20 years. The IDA-5 is a full-featured device that measures instantaneous flow, average flow, occlusion pressure and dual flow based on IEC60601-2-24.

The IDA-5 has built-in automation allowing users to create custom test templates for quick, standardized infusion pump analysis with minimal user intervention. The IDA-5 test automation bundle includes Ansur software for comprehensive testing.

Automated testing allows technicians to set up tests and walk away. It is easy to set up and requires little or no training to use. The IDA-5 can be used to test a wide variety of infusion pumps including volumetric pumps, syringe pumps, PCA pumps, drip-rate pumps, anesthesia pumps and ambulatory pumps. The IDA-5 maximizes productivity with multiple, independent channels for testing up to four infusion pumps at once.

With its built-in memory, the IDA-5 records test results internally, and provides easy-to-read graphs right on the analyzer's screen. Additionally, an auto-start feature simplifies syringe pump testing as well as other tests with long startup times. And the color display is so large numbers can be read from across the room. The IDA-5 also comes with Hydrograph PC software for creating full-color graphs and reports, and is compatible with plug 'n play accessories such as barcode scanners, keyboards and printers.



Key features

- Tests up to four infusion pumps at the same time
- Customizable test templates for quick and standardized testing
- On-board and PC-based automation
- Compatible with virtually any type of infusion device
- Real time snap shots of flow and pressure for immediate issue recognition
- Instantaneous and average flow measurement of up to 1500 ml/hr
- Occlusion pressure measurements to 45 psi
- Single-flow, dual-flow (piggyback) and PCA testing
- Auto-start mode enables unit to begin testing only when fluid is detected to maximize accuracy
- Ability to automatically end flow measurement based on user-defined time, volume or both
- Convenient and easy data entry with plug 'n play, USB compatible keyboard or barcode scanner
- Built-in memory to save test results for printing or downloading to computer
- Optional Ansur automation software completely integrates medical device testing including electrical safety, visual inspection and other performance parameters for total digital data management
- Global support network delivering prompt service worldwide

HydroGraph™ Graphics Software.

Use the moving color visuals of HydroGraph to troubleshoot up to four infusion pumps at once. Data is taken directly off the transducer and transmitted to HydroGraph. The flowing graphs provide an electronic means to display, store and recall flow patterns for comparison at a later date. Each test window can display instantaneous and average flow rates, cumulative and bolus volumes, and occlusion pressure.

Technical specifications

Flow rate measurement	
Technique	Flow is calculated by measuring volume over time
Range	0.1 ml/h to 1500 ml/h (2500 ml/h is shown)
Accuracy	1 % of reading \pm 1 LSD for flows of 16 to 200 ml/h for volumes over 20 ml, otherwise 2 % of reading \pm 1 LSD for volumes over 10 ml under laboratory conditions. Degassed water at 15 °C to 30 °C (59 °F to 86 °F) is recommended for long tests.
Max test duration	100 hours
Volume measurement	
Technique	Volume is measured directly by the measuring module in minimum sample sizes of 60 μ l
Range	0.06 ml to 9999 ml
Accuracy	1 % of reading \pm 1 LSD for flow rates of 16 ml/h to 200 ml/h for volumes over 20 ml. Otherwise 2 % of reading \pm 1 LSD for volumes over 10 ml under laboratory conditions.
Max test duration	100 hours
PCA bolus/dual flow measurement	
Method	See volume measurement above
Min bolus volume	0.5 ml
Resolution	60 μ l increments
Max test duration	100 hours
Pressure measurement	
Method (back pressure and flow test)	Direct measurement of pressure at the inlet port
Range	0 psi to 45 psi and equivalent in mmHg, Bar and kPa
Accuracy	1 % of Full Scale \pm 1 LSD under laboratory conditions
Max test duration	1 hour
Other specification	
Templates	Predetermined test sequences. Typical capacity 200.
Storage of results	Test results stored for later viewing, printing or transfer to PC.

General specifications

Operating voltage range	100 V ac to 240 V ac
Supply frequency	50/60 Hz
Supply power	<50 VA
Fuses	20 mm T1.6 A H 250 V x 2
Size (HxWxD)	30 cm x 20 cm x 20 cm (12 in x 8 in x 8 in)
Weight	3.4 kg (approx) (7.5 lbs.)
Altitude	0 m to 3000 m (0 ft to 10000 ft)
Temperature	
Operating	15 °C to 30 °C (59 °F to 86 °F)
Storage	-20 °C to +40 °C (-4 °F to +104 °F) when drained of all liquid
Humidity	10 % to 90 % non-condensing

Ordering information

Models	Model Description
4349304	IDA-5/1 US120V One-Channel Infusion Device Analyzer, US
4349337	IDA-5/1 AUS250V One-Channel Infusion Device Analyzer, Australia
4349343	IDA-5/1 DEN250V One-Channel Infusion Device Analyzer, Denmark
4349355	IDA-5/1 SHK250V One-Channel Infusion Device Analyzer, Shuko
4349362	IDA-5/1 ISR250V One-Channel Infusion Device Analyzer, Israel
4349370	IDA-5/1 ITAL250V One-Channel Infusion Device Analyzer, Italy
4349381	IDA-5/1 IND250V One-Channel Infusion Device Analyzer, India
4349396	IDA-5/1 SWZ250V One-Channel Infusion Device Analyzer, Switzerland
4349409	IDA-5/1 UK250V One-Channel Infusion Device Analyzer, UK
4349411	IDA-5/1 BRAZ230V One-Channel Infusion Device Analyzer, Brazil
4349319	IDA-5/2 US120V Two-Channel Infusion Device Analyzer, US
4349427	IDA-5/2 AUS250V Two-Channel Infusion Device Analyzer, Australia
4349430	IDA-5/2 DEN250V Two-Channel Infusion Device Analyzer, Denmark
4349448	IDA-5/2 SHK250V Two-Channel Infusion Device Analyzer, Shuko
4349453	IDA-5/2 ISR250V Two-Channel Infusion Device Analyzer, Israel
4349466	IDA-5/2 ITAL250V Two-Channel Infusion Device Analyzer, Italy
4349475	IDA-5/2 IND250V Two-Channel Infusion Device Analyzer, India
4349482	IDA-5/2 SWZ250V Two-Channel Infusion Device Analyzer, Switzerland
4349494	IDA-5/2 UK250V Two-Channel Infusion Device Analyzer, UK
4349516	IDA-5/2 BRAZ230V Two-Channel Infusion Device Analyzer, Brazil
4349328	IDA-5/4 US120V Four-Channel Infusion Device Analyzer, US
4349525	IDA-5/4 AUS250V Four-Channel Infusion Device Analyzer, Australia
4349533	IDA-5/4 DEN250V Four-Channel Infusion Device Analyzer, Denmark
4349540	IDA-5/4 SHK250V Four-Channel Infusion Device Analyzer, Shuko
4349557	IDA-5/4 ISR250V Four-Channel Infusion Device Analyzer, Israel
4349569	IDA-5/4 ITAL250V Four-Channel Infusion Device Analyzer, Italy
4349584	IDA-5/4 IND250V Four-Channel Infusion Device Analyzer, India
4349591	IDA-5/4 SWZ250V Four-Channel Infusion Device Analyzer, Switzerland
4349600	IDA-5/4 UK250V Four-Channel Infusion Device Analyzer, UK
4349617	IDA-5/4 BRAZ230V Four-Channel Infusion Device Analyzer, Brazil

Ordering information continued

Standard accessories	
4418071	Hydrograph Software and Users Manual
4354014	20 ml syringe
4354038	3-way plastic Luerlock
4478942	5-ft plastic drain line
4541948	Micro-90 bottle (225 ml)
4354452	USB data transfer cable
Optional accessories	
4354490	Optional miniature keyboard
4354503	Ansur Test Software, IDA-5 plug-in license
4354532	One-channel upgrade option

About Fluke Biomedical

Fluke Biomedical is the world's leading manufacturer of quality biomedical test and simulation products. In addition, Fluke Biomedical provides the latest medical imaging and oncology quality-assurance solutions for regulatory compliance. Highly credentialed and equipped with a NVLAP Lab Code 200566-0 accredited laboratory, Fluke Biomedical also offers the best in quality and customer service for all your equipment calibration needs.

Today, biomedical personnel must meet the increasing regulatory pressures, higher quality standards, and rapid technological growth, while performing their work faster and more efficiently than ever. Fluke Biomedical provides a diverse range of software and hardware tools to meet today's challenges.

Fluke Biomedical regulatory commitment

As a medical test device manufacturer, we recognize and follow certain quality standards and certifications when developing our products. We are ISO 9001 and ISO 13485 medical device certified and our products are:

- CE Certified, where required
- NIST Traceable and Calibrated
- UL, CSA, ETL Certified, where required
- NRC Compliant, where required



绿测科技有限公司

广州总部：广州市番禺区陈边村金欧大道83号江潮创意园A栋208室
 深圳分公司：深圳市龙华区龙华街道 油松社区东环一路1号耀丰通工业园1-2栋2栋507
 南宁分公司：广西自由贸易试验区南宁片区五象大道401号五象航洋城1号楼3519号
 广州分公司：广州市南沙区凤凰大道89号中国铁建·凤凰广场B栋1201房
 电话：020-2204 2442
 传真：020-8067 2851
 邮箱：Sales@greentest.com.cn
 官网：www.greentest.com.cn



微信视频号



绿测科技订阅号



绿测工场服务号

